

Type.....	57961
Designation.....	Power Bank
Systems to charge.....	Lithium-Ion / 3.7 V / 4 pcs.
Cell configurations.....	10400 mAh, 38.48 Wh
Housing Material:	ABS
Dimensions:	Charger:
Length.....	105 +- 1 mm
Width.....	80 +- 1 mm
Height.....	23 +- 1mm
Weight.....	240.5 g



Charging methods:	Plug in Micro USB port:	Maintenance Charge:
Input.....	Current: 500 - 2000 mA	N/A
Discharging methods:	USB port for charging other devices	
Output.....	5.0 V, 1000 mA and 2400 mA	

Indications for IN:	
During Charge.....	LEDs indicate level of charge and next level is flashing. LEDs flashes at the rate of 0.5 sec/cycle.
Charge completed.....	LEDs on

Indications for OUT:	
5 Blue LED	81 - 100 % Capacity
4 Blue LED.....	61 - 80 % Capacity
3 Blue LED.....	41 - 60 % Capacity
2 Blue LED.....	20 - 41 % Capacity
1 Blue LED.....	< 20 % Capacity

Ambient temperature:	
Charge.....	0 - +45 °C
Discharge.....	-20 - +45 °C
Storage.....	-20 - +45 °C

Cut off criteria:	
Li-Ion cells.....	Stop discharging, when Li-Ion voltage lower than 2.8 V Short circuit protection Overload protection

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries